Product data sheet Characteristics

NSYS3D7525P

Spacial S3D plain door with mount.plate. H700xW500xD250.IP66 IK10 RAL7035.





Main

Main		S
Range	Spacial	
Product name	Spacial S3D	Ť
Application	Multi-purpose	
Category	Compact enclosure	
Enclosure nominal height	700 mm	±i;
Enclosure nominal width	500 mm	<u>.</u>
Enclosure nominal depth	250 mm	
Door type	Plain	ide:
Mounting plate description	Plain	
Type of gland plate	Standard	E
Installation accessory type	Wall-mounting	
Device composition	1 body 1 mounting plate 1 door with lock 1 cable gland plate	of to best of for

Complementary

Body type	Gutter-shaped front rail double sheet thickness Single piece body	
Number of doors	Front face: 1 door(s)	
Door opening side	Reversible (120 °)	
Lock type	3 points lock, 3 mm double-bar	
Accessibility for operation	n Front	
Removable parts	Door by hinges Cable gland plate by screws Mounting plate by fixing element	
Material	Enclosure: steel Mounting plate: galvanised steel	

Surface finish	Enclosure: epoxy-polyester powder Enclosure: grey (RAL 7035)	
Colour		
Standards	IEC 62208	
Product certifications	CUL GL LR UL DNV BV	
Net weight	19 kg	

Environment

IK degree of protection	IK10 conforming to IEC 62262	
IP degree of protection	IP66 conforming to IEC 60529	

Packing Units

PCE
1
19 kg
71.3 cm
51.8 cm
29.8 cm

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	
alifornia proposition 65 WARNING: This product can expose you to chemicals including: Lead and lead compounds is known to the State of California to cause cancer and birth defects or other reproductive h more information go to www.P65Warnings.ca.gov		

Contractual warranty

	-	
Warranty	18 month	S
•		